

Technical Specifications for Hand Propelled Thermoplastic Road Marking Machine, Road Marking Remover and Other Accessories



1. Hand Propelled Thermoplastic Road Marking Machine

Parameters	Description
Physical Characteristics	<ul style="list-style-type: none"> Weight: 100 kg - 150 kg Dimension: (L: 1000 mm – 1500 mm) × (W: 600 mm – 1000 mm) × (H: 900 mm – 1500 mm)
Thermoplastic Tank	<ul style="list-style-type: none"> Capacity: 90 kg – 150 kg Material: Stainless Steel Temperature Gauge: Yes
Power Source	Manual Propulsion
Glass Bead Dispenser	<ul style="list-style-type: none"> Material: Stainless Steel Adjustable Width Should Dispense Glass Beads at Constant Rate irrespective of the speed of the machine and Rate Of Discharge of the glass beads should be adjustable
Glass Bead Capacity	10 kg – 50 kg
Heating System	<ul style="list-style-type: none"> LPG Burner Safety Features Should be Provided
Screed Shoe	Adjustable Screed Shoe
Additional Features	<ul style="list-style-type: none"> Adjustable Handlebar Accessory Holders
Warranty	Yes, 1 Year Minimum

2. Road Marking Remover

Parameters	Description
Physical Characteristics	<ul style="list-style-type: none"> Weight: 100 kg - 150 kg Dimension: (L: 800 mm – 1200 mm) × (W: 400 mm – 700 mm) × (H: 850 mm – 1200 mm)
Power	9 HP to 13 HP
Engine	Gasoline or Electric
Rotation Speed	2000 rpm to 4000 rpm
Working Width	150 mm to 300 mm
Removing Depth	0 mm to 5 mm
Driving Method	Self-propelled
Blades Included	Yes, mandatorily
Warranty	Yes, 1 Year Minimum

Handwritten signature

श. अनुकुल निधि
सहायक विज्ञ
शहरी योजना आयोग

Handwritten signature

Handwritten signature
६/८
इ. निर्मल राज बराल
उप-निर्देशक